

	TECHNICAL DATA SHEET	Doc No.	AP/QA/TDS/01																																				
		Rev No.	0																																				
		Date	01-06-25																																				
PRODUCT NAME Crumb Rubber 30 Mesh																																							
Product description Free-flowing, homogeneous and uniform, black rubber powder with devoid of iron/steel and fiber derived from 100% Truck & Bus radial ELT's through ambient grinding.																																							
Contact Data of Manufacturer <table border="1" style="width: 100%;"> <tr> <td style="width: 20%;">NAME</td> <td>AP GROUP</td> </tr> <tr> <td rowspan="2">PLANT</td> <td>AP Rubber Industries, Haridwar, Uttarakhand, India</td> </tr> <tr> <td>A P Recyclers (SFZ) LLC Salah Freezone, Salah, Oman</td> </tr> <tr> <td>Tel</td> <td>.+91 9837473436, +91 8057714990</td> </tr> <tr> <td rowspan="2">E-mail</td> <td>arvind@aprubberindustries.com</td> </tr> <tr> <td>abhishek@aprubberindustries.com</td> </tr> </table>				NAME	AP GROUP	PLANT	AP Rubber Industries, Haridwar, Uttarakhand, India	A P Recyclers (SFZ) LLC Salah Freezone, Salah, Oman	Tel	.+91 9837473436, +91 8057714990	E-mail	arvind@aprubberindustries.com	abhishek@aprubberindustries.com																										
NAME	AP GROUP																																						
PLANT	AP Rubber Industries, Haridwar, Uttarakhand, India																																						
	A P Recyclers (SFZ) LLC Salah Freezone, Salah, Oman																																						
Tel	.+91 9837473436, +91 8057714990																																						
E-mail	arvind@aprubberindustries.com																																						
	abhishek@aprubberindustries.com																																						
Typical Properties <table border="1" style="width: 100%;"> <thead> <tr> <th>Properties</th> <th>Specification</th> <th>Unit</th> <th>Test Methods</th> </tr> </thead> <tbody> <tr> <td>Polymer</td> <td colspan="3" style="text-align: center;">Natural Rubber</td> </tr> <tr> <td>Specific gravity</td> <td>1.13-1.15</td> <td>N/A</td> <td>ASTM D-1817</td> </tr> <tr> <td>Moisture</td> <td>1.5 Max</td> <td>%</td> <td>ASTM D-297</td> </tr> <tr> <td>Sieve passing 30 mesh (595 micron)</td> <td>95 Min</td> <td>%</td> <td>ASTM D-5644</td> </tr> <tr> <td>Rubber Hydrocarbon</td> <td>45 Min</td> <td>%</td> <td>ASTM D-297</td> </tr> <tr> <td>Ash content</td> <td>8 Max</td> <td>%</td> <td>ASTM D-297</td> </tr> <tr> <td>Carbon black content</td> <td>32 Max</td> <td>%</td> <td>ASTM D-297</td> </tr> <tr> <td>Acetone Extract</td> <td>14 Max</td> <td>%</td> <td>ASTM D-297</td> </tr> </tbody> </table>				Properties	Specification	Unit	Test Methods	Polymer	Natural Rubber			Specific gravity	1.13-1.15	N/A	ASTM D-1817	Moisture	1.5 Max	%	ASTM D-297	Sieve passing 30 mesh (595 micron)	95 Min	%	ASTM D-5644	Rubber Hydrocarbon	45 Min	%	ASTM D-297	Ash content	8 Max	%	ASTM D-297	Carbon black content	32 Max	%	ASTM D-297	Acetone Extract	14 Max	%	ASTM D-297
Properties	Specification	Unit	Test Methods																																				
Polymer	Natural Rubber																																						
Specific gravity	1.13-1.15	N/A	ASTM D-1817																																				
Moisture	1.5 Max	%	ASTM D-297																																				
Sieve passing 30 mesh (595 micron)	95 Min	%	ASTM D-5644																																				
Rubber Hydrocarbon	45 Min	%	ASTM D-297																																				
Ash content	8 Max	%	ASTM D-297																																				
Carbon black content	32 Max	%	ASTM D-297																																				
Acetone Extract	14 Max	%	ASTM D-297																																				
Remarks 																																							
Created By		Checked By																																					
		Approved By																																					

	TECHNICAL DATA SHEET		Doc No.	AP/QA/TDS/02
			Rev No.	0
			Date	01-06-25
PRODUCT NAME Crumb Rubber 40 Mesh				
Product description Free-flowing, homogeneous and uniform, black rubber powder with devoid of iron/steel and fiber derived from 100% Truck & Bus radial ELT's through ambient grinding.				
Contact Data of Manufacturer				
NAME	AP GROUP			
PLANT	AP Rubber Industries, Haridwar, Uttarakhand, India A P Recyclers (SFZ) LLC Salah Freezone, Salah, Oman			
Tel	.+91 9837473436, +91 8057714990			
E-mail:	arvind@aprubberindustries.com abhishek@aprubberindustries.com			
Typical Properties				
Properties	Specification	Unit	Test Methods	
Polymer	Natural Rubber			
Specific gravity	1.13-1.15	N/A	ASTM D-1817	
Moisture	1.5 Max	%	ASTM D-297	
Sieve passing 40 mesh (400 micron)	85 Min	%	ASTM D-5644	
Rubber Hydrocarbon	45 Min	%	ASTM D-297	
Ash content	9 Max	%	ASTM D-297	
Carbon black content	32 Max	%	ASTM D-297	
Acetone Extract	14 Max	%	ASTM D-297	
Remarks				
Created By Checked By Approved By				



TECHNICAL DATA SHEET

Doc No.	AP/QA/TDS/03
Rev No.	0
Date	01-06-25

PRODUCT NAME

Crumb Rubber 50 Mesh

Product description

Free-flowing, homogeneous and uniform, black rubber powder with devoid of iron/steel and fiber derived from 100% Truck & Bus radial ELT's through ambient grinding.

Contact Data of Manufacturer

NAME	AP GROUP
PLANT	AP Rubber Industries, Haridwar, Uttarakhand, India
	A P Recyclers (SFZ) LLC Salah Freezone, Salah, Oman
Tel	.+91 9837473436, +91 8057714990
E-mail:	arvind@aprubberindustries.com
	abhishek@aprubberindustries.com

Typical Properties

Properties	Specification	Unit	Test Methods
Polymer	Natural Rubber		
Specific gravity	1.13-1.15	N/A	ASTM D-1817
Moisture	1.5 Max	%	ASTM D-297
Sieve passing 50 Mesh	80 Min	%	ASTM D-5644
Rubber Hydrocarbon	45 Min	%	ASTM D-297
Ash content	10 Max	%	ASTM D-297
Carbon black content	32 Max	%	ASTM D-297
Acetone Extract	14 Max	%	ASTM D-297

Remarks

--

Created By	Checked By	Approved By
------------	------------	-------------

	TECHNICAL DATA SHEET		Doc No.	AP/QA/TDS/04																																				
			Rev No.	0																																				
			Date	01-06-25																																				
PRODUCT NAME Crumb Rubber 60 Mesh																																								
Product description Free-flowing, homogeneous and uniform, black rubber powder with devoid of iron/steel and fiber derived from 100% Truck & Bus radial ELT's through ambient grinding.																																								
Contact Data of Manufacturer <table border="1" style="width: 100%;"> <tr> <td style="width: 15%;">NAME</td> <td>AP GROUP</td> </tr> <tr> <td>PLANT</td> <td>AP Rubber Industries, Haridwar, Uttarakhand, India A P Recyclers (SFZ) LLC Salah Freezone, Salah, Oman</td> </tr> <tr> <td>Tel</td> <td>+91 9837473436, +91 8057714990</td> </tr> <tr> <td>E-mail:</td> <td>arvind@aprubberindustries.com abhishek@aprubberindustries.com</td> </tr> </table>					NAME	AP GROUP	PLANT	AP Rubber Industries, Haridwar, Uttarakhand, India A P Recyclers (SFZ) LLC Salah Freezone, Salah, Oman	Tel	+91 9837473436, +91 8057714990	E-mail:	arvind@aprubberindustries.com abhishek@aprubberindustries.com																												
NAME	AP GROUP																																							
PLANT	AP Rubber Industries, Haridwar, Uttarakhand, India A P Recyclers (SFZ) LLC Salah Freezone, Salah, Oman																																							
Tel	+91 9837473436, +91 8057714990																																							
E-mail:	arvind@aprubberindustries.com abhishek@aprubberindustries.com																																							
Typical Properties <table border="1" style="width: 100%;"> <thead> <tr> <th style="width: 35%;">Properties</th> <th style="width: 25%;">Specification</th> <th style="width: 10%;">Unit</th> <th style="width: 30%;">Test Methods</th> </tr> </thead> <tbody> <tr> <td>Polymer</td> <td colspan="3">Natural Rubber</td> </tr> <tr> <td>Specific gravity</td> <td>1.13-1.15</td> <td>N/A</td> <td>ASTM D-1817</td> </tr> <tr> <td>Moisture</td> <td>1.5 Max</td> <td>%</td> <td>ASTM D-297</td> </tr> <tr> <td>Sieve passing 60 mesh (250 micron)</td> <td>90 Min</td> <td>%</td> <td>ASTM D-5644</td> </tr> <tr> <td>Rubber Hydrocarbon</td> <td>45 Min</td> <td>%</td> <td>ASTM D-297</td> </tr> <tr> <td>Ash content</td> <td>10 Max</td> <td>%</td> <td>ASTM D-297</td> </tr> <tr> <td>Carbon black content</td> <td>32 Max</td> <td>%</td> <td>ASTM D-297</td> </tr> <tr> <td>Acetone Extract</td> <td>14 Max</td> <td>%</td> <td>ASTM D-297</td> </tr> </tbody> </table>					Properties	Specification	Unit	Test Methods	Polymer	Natural Rubber			Specific gravity	1.13-1.15	N/A	ASTM D-1817	Moisture	1.5 Max	%	ASTM D-297	Sieve passing 60 mesh (250 micron)	90 Min	%	ASTM D-5644	Rubber Hydrocarbon	45 Min	%	ASTM D-297	Ash content	10 Max	%	ASTM D-297	Carbon black content	32 Max	%	ASTM D-297	Acetone Extract	14 Max	%	ASTM D-297
Properties	Specification	Unit	Test Methods																																					
Polymer	Natural Rubber																																							
Specific gravity	1.13-1.15	N/A	ASTM D-1817																																					
Moisture	1.5 Max	%	ASTM D-297																																					
Sieve passing 60 mesh (250 micron)	90 Min	%	ASTM D-5644																																					
Rubber Hydrocarbon	45 Min	%	ASTM D-297																																					
Ash content	10 Max	%	ASTM D-297																																					
Carbon black content	32 Max	%	ASTM D-297																																					
Acetone Extract	14 Max	%	ASTM D-297																																					
Remarks																																								
Created By		Checked By		Approved By																																				